



CHARM FOR GOFORM TIRES



PASSENGER AND LIGHT TRUCK TIRE CATALOGUE 2022

UHP / HP / SUV / AT / MT / WINTER TIRE



CHARM FOR GOFORM TIRES

COMPANY PROFILES

G-521		01-02
GH18		03-04
G-866		05-06
G-326		07-08
G-520		09-10
G-745		11-12
G-325		13-14
G-668		15-16
AT-01		17-18
GT-02		19-20
GS-03		21-22
GF-50		23-24
GM-02		25-26
W705		27-28
W766		29-30
W696		31-32
BRAVES AU518	...	33-34
LX-50		35-36

CONTENTS

HP	UHP	UHP
G-521	GH-18	G-866
		

SUV	SUV	SUV
GT-02	GS-03	GF-50
		

LTR	HP	UHP
G-326	G-520	G-745
		

MT	WINTER	WINTER
GM-02	W705	W766
		

LTR	UHP	SUV
G-325	G-668	AT-01
		

WINTER	UHP	LTR
W696	BRAVES AU518	LX-50
		

G - 5 2 1

G-521



The unique formula and pattern design of the tread compound makes the vehicle more precise control and excellent silent comfort.

Not only that, but the G521 is excellent in both dry and wet conditions, as well as silencing.

It is a kind of high comprehensive performance tire that can bring joy to driving life.



Size	LI	SS	XL	Overall Diameter	Section Width	Standard Rim	Max. Load	Max. Pressure
				mm	mm		kg	kPa
155/70R13	75	T	–	548	157	4.5	387	300
155/80R13	79	T	–	578	157	4.5	437	300
165/65R13	77	T	–	544	170	5.0	387	300
165/70R13	79	T	–	562	170	5.0	437	300
175/60R13	77	T	–	540	177	5.0	412	300
175/70R13	82	T	–	576	177	5.0	475	300
155/65R14	75	T	–	558	157	4.5	387	300
165/60R14	75	H	–	554	170	5.0	387	300
165/65R14	79	T	–	570	170	5.0	437	300
165/70R14	81	T	–	588	170	5.0	462	300
175/65R14	82	H	–	584	177	5.0	475	300
175/70R14	84	T	–	602	177	5.0	500	300
185/55R14	80	H	–	560	194	6.0	450	300
185/60R14	82	H	–	578	189	5.5	475	300
185/65R14	86	H	–	596	189	5.5	530	300
185/70R14	88	T	–	616	189	5.5	560	300
195/70R14	91	T	–	630	201	6.0	615	300
175/60R15	81	V	–	591	177	5.0	462	300
175/65R15	84	H	–	609	177	5.0	500	300
185/55R15	82	V	–	585	194	6.0	475	300
185/60R15	84	H	–	603	189	5.5	500	300
185/65R15	88	H	–	621	189	5.5	560	300
195/50R15	82	V	–	577	201	6.0	475	300
195/55R15	85	V	–	595	201	6.0	515	300
195/60R15	88	H	–	615	201	6.0	560	300
195/65R15	91	H	–	635	201	6.0	615	300
205/60R15	91	V	–	627	209	6.0	615	300
205/65R15	94	H	–	647	209	6.0	670	300
195/55R16	87	V	–	620	201	6.0	545	300
205/55R16	91	V	–	632	214	6.5	615	300
205/60R16	92	V	–	652	209	6.0	630	300
215/60R16	95	V	–	664	221	6.0	690	300
215/65R16	98	H	–	686	221	6.5	750	300

HIGH PERFORMANCE
AND MODIFIED CAR SERIES



GH-18

GH-18



Unique tire tread formulation and the pattern design enable the vehicle to have more precision manoeuvrability and better quiet comfort.
In addition, GH-18 plays well in both wet and dry conditions while driving with low noise and is of high comprehensive performance which can bring your life much fun.



Size	LI	SS	XL
195/45R15	78	V	-
195/45R16	84	V	XL
195/50R16	84	V	-
205/40Zr17	84	W	XL
205/45R17	88	V	XL
205/45Zr16	87	W	XL
205/50R16	87	V	-
205/50Zr17	93	W	XL
205/55Zr16	91	W	-
205/55Zr17	95	W	XL
205/60R16	92	H	-
205/60R16	92	V	-
205/60R16	96	V	XL
205/60R16	96	H	XL
205/60R17	94	H	-
205/65R16	95	H	-
215/35Zr18	84	W	XL
215/40Zr16	86	W	XL
215/45Zr16	90	W	XL
215/45Zr17	91	W	XL
215/45Zr18	93	W	XL
215/50Zr17	91	W	-
215/55R16	97	V	XL
215/55R17	94	V	-
215/55Zr17	98	W	XL
215/55Zr18	99	W	XL
215/60R16	95	V	-
215/60R16	99	V	XL
215/60R17	96	H	-
225/35Zr20	90	W	XL
225/40Zr18	92	W	XL
225/40Zr19	93	W	XL
225/45Zr17	94	W	XL
225/45Zr18	95	W	XL
225/45Zr19	92	W	-
225/50Zr16	92	W	-
225/50Zr17	98	W	XL
225/55R16	99	V	XL
225/55R16	95	V	-
225/55R18	98	V	-
225/55Zr16	95	W	-
225/55Zr16	99	W	XL
225/55Zr17	97	W	-
225/55Zr17	101	W	XL
225/60R16	98	H	-
225/60R16	102	H	XL
225/60R16	102	V	XL
225/60R17	99	H	-
225/60R18	100	H/V	-
225/65R17	102	H	-
235/35Zr19	91	W	XL

Size	LI	SS	XL
235/40Zr18	95	W	XL
235/40Zr19	96	W	XL
235/45Zr17	97	W	XL
235/45Zr18	98	W	XL
235/50Zr17	96	W	-
235/50Zr18	101	W	XL
235/50Zr19	103	W	XL
235/55R17	99	V	-
235/55Zr18	104	W	XL
235/55Zr19	101	W	-
235/55Zr20	105	W	XL
235/60R16	100	H	-
235/60R18	103	H	-
245/30Zr20	97	W	XL
245/30Zr20	90	W	XL
245/35Zr19	93	W	XL
245/35Zr20	95	W	XL
245/40Zr18	97	W	XL
245/40Zr19	98	W	XL
245/45Zr17	99	W	XL
245/45Zr18	100	W	XL
245/45Zr19	102	W	XL
245/45Zr20	103	W	XL
245/50Zr18	104	W	XL
245/50Zr20	102	W	-
245/55Zr19	103	W	-
255/35Zr19	96	W	XL
255/40Zr18	99	W	XL
255/40Zr19	100	W	XL
255/45R20	105	V	XL
255/45Zr17	102	W	XL
255/45Zr18	103	W	XL
255/45Zr19	104	W	XL
255/50Zr19	107	W	XL
255/50Zr20	109	W	XL
255/55Zr19	107	W	-
255/55Zr20	110	W	XL
265/35Zr18	97	W	XL
265/50Zr19	110	W	XL
275/30Zr20	97	W	XL
275/35Zr19	100	W	XL
275/40Zr19	105	W	XL
275/40Zr20	106	W	XL
275/45R20	110	V	XL
275/45Zr18	107	W	XL
275/45Zr19	108	W	XL
275/45Zr21	110	W	XL
275/50Zr20	113	W	XL
275/55Zr19	111	W	XL
295/40Zr21	111	W	XL

SUPERABRASION SERIES

G - 8 6 6



Comfort



Fuel-saving



Silence



Safety

Ensuring excellent durability, the comfortability and reliable control performance of the vehicles and vehicles can be improved to the greatest extent.

Longer mileage, more wear – resistant.
The formula of tread rubber is optimized to improve wear life and ensure longer form distance.

Is safe and durable with high performance.
While improving the wear resistance, it meets the economic, safety and maneuverability requirements of compact cars.

G-866

Size	LI	SS	XL	Overall Diameter	Section Width	Standard Rim	Max. Load	Max. Pressure
				mm	mm		kg	kPa
245/60R18	105	V	–	751	248	7.0	925	300
255/55R18	109	W	XL	737	265	8.0	1030	340
285/60R18	120	V	XL	799	292	8.5	1400	340
235/65R19	109	V	XL	789	240	7.0	1030	340
265/40ZR20	104	W	XL	720	271	9.5	900	340
265/50R20	111	W	XL	774	277	8.5	1090	340
275/40ZR20	106	W	XL	728	278	9.5	950	340
275/45ZR20	110	W	XL	756	273	9.0	1060	340
285/50R20	116	W	XL	794	297	9.0	1250	340
265/40ZR21	105	W	XL	745	271	9.5	925	340
285/35ZR22	106	W	XL	759	290	10.0	950	340
305/40ZR22	114	W	XL	803	313	11.0	1180	340
315/35ZR22	111	W	XL	779	320	11.0	1090	340



G-326



G - 3 2 6



Comfort



Fuel-saving



Silence



Safety

The wide shoulder design enhances wetland grip.

Super wide tread contact drive smooth,comfortable and tire durable.

Special wear-resistant formula.

Low noise and low fuel consumption.

Size	LI	SS	XL	Overall Diameter	Section Width	Standard Rim	Max. Load	Max. Pressure
				mm	mm		kg	kPa
185/R14C	102/100	T	–	652	189	5.5	850/800	450
195/R14C	106/104	T	–	668	196	5.5	950/900	450
195/70R15C	104/102	T	–	655	201	6	900/850	450
205/65R15C	102/100	T	–	647	209	6	850/800	375
225/70R15C	112/110	T	–	697	228	6.5	1120/1060	450
215/70R15C	109/107	T	–	683	221	6.5	1030/975	450
195/65R16C	104/102	T	–	660	201	6	900/850	475
205/65R16C	107/105	T	–	672	209	6	975/925	475
215/65R16C	109/107	T	–	686	221	6.5	1030/975	475
225/65R16C	112/110	T	–	698	228	6.5	1120/1060	475
235/65R16C	115/113	T	–	712	240	7	1215/1150	475
195/75R16C	107/105	T	–	698	196	5.5	975/925	475
185/75R16C	104/102	T	–	684	184	5	900/850	475
205/75R16C	110/108	T	–	714	203	5.5	1060/1000	475
215/75R16C	113/111	T	–	728	216	6	1150/1090	475



G - 5 2 0



Silence



Drainage



Handling



Safety

The unique formula and pattern design of the tread compound makes the vehicle more precise control and excellent silent comfort.

Not only that, but the G520 is excellent in both dry and wet conditions, as well as silencing.

It is a kind of high comprehensive performance tire that can bring joy to driving life.



G-520

Size	LI	SS	XL	Overall Diameter	Section Width	Standard Rim	Max. Load	Max. Pressure
				mm	mm		kg	kPa
145/60R13	66	T	-	504	150	4.5	300	300
145/70R12	69	T	-	509	150	4.5	325	300
155/65R13	73/77	T	-	532	157	4.5	365	300
155/65R14	75	T	-	558	157	4.5	387	300
155/70R13	75	T	-	548	157	4.5	387	300
155/80R13	79	T	-	578	157	4.5	437	300
165/60R14	75	H	-	554	170	5.0	387	300
165/65R13	77	T	-	544	170	5.0	412	300
165/65R14	79	T	-	570	170	5.0	437	300
165/70R13	79	T	-	562	170	5.0	437	300
165/70R14	81	T/H	-	588	170	5.0	462	300
175/60R13	77	T	-	576	177	5.0	412	300
175/60R14	79	T	-	566	177	5.0	437	300
175/65R13	80	T	-	558	177	5.0	450	300
175/65R14	82/86	T/H	XL	584	177	5.0	475	300
175/65R15	84	H	-	609	177	5.0	500	300
175/70R13	82	T/H	-	576	177	5.0	475	300
175/70R14	84	H/T	-	602	177	5.0	500	300
175/70R14	88	T/H	XL	602	177	5.0	560	340
185/60R14	82	H/T	-	578	189	5.5	475	300
185/60R15	82/84/88	H	XL	603	189	5.5	500	300
185/65R14	86	H/T	-	596	189	5.5	530	300
185/65R15	88	H/T	-	621	189	5.5	560	300
185/70R13	86	T	-	590	189	5.5	530	300
185/70R14	88	H/T	-	616	189	5.5	560	300
195/60R14	86	T/H	-	590	201	6.0	530	300
195/65R14	89	H	-	610	201	6.0	580	300
195/70R14	91	H/T	-	630	201	6.0	615	300
205/70R14	98	H	XL	644	209	6.0	750	340

HIGH PERFORMANCE TIRES



G-745



G - 7 4 5



Silence



Drainage



Handling



Safety

Better driving and handing performance.

The pattern is specially designed for improving the performance of driving, controlling and dry wetland.

Silicon-containing formula improves control and braking performance, reduces noise, reduces rolling resistance, reduces heat generation and increases range.



Size	LI	SS	XL	Overall Diameter	Section Width	Standard Rim	Max. Load	Max. Pressure
				mm	mm		kg	kPa
185/55R15	82	V	–	585	194	6.0	475	300
195/50R15	82	V/H	–	577	201	6.0	475	300
195/55R15	85	H/V	–	595	201	6.0	515	300
195/60R15	88	V/H	–	615	201	6.0	560	300
195/65R15	91/95	V/H	XL	635	201	6.0	615	300
205/50R15	89	V	XL	587	214	6.5	580	340
205/55R16	91/94	V/H	XL	632	214	6.5	600	300
205/55ZR16	91/94	W	XL	632	214	6.5	600	300
205/60R15	91	H	–	627	209	6.0	615	300
205/65R15	94	V/H	–	647	209	6.0	670	300
215/55R16	93/97	V	XL	642	226	7.0	650	300
215/55ZR16	97	W	XL	642	226	7.0	730	350
215/60R15	94	V	–	639	221	6.5	670	300
215/60R16	95	H/V	–	664	221	6.5	690	300
215/65R15	100	H	–	661	221	6.5	670	300
215/65R16	98	V/H	–	686	221	6.5	750	300
215/70R15	98	H	–	683	221	6.5	750	300



G - 3 2 5



Comfort



Fuel-saving



Silence



Safety

The wide shoulder design enhances wetland grip.

Super wide tread contact drive smooth,comfortable and tire durable.

Special wear-resistant formula.

Low noise and low fuel consumption.



G-325

Size	LI	SS	XL	Overall Diameter	Section Width	Standard Rim	Max. Load	Max. Pressure
				mm	mm		kg	kPa
155R12C	83/81	N	-	553	157	4.5	487/462	350
155R13C	85/83	P/Q	-	578	157	4.5	487/462	350
165/70R13C	88/86	P/R	-	562	170	5.0	560/530	375
165R13C	89/88/94/93	P/R	-	594	165	4.5	580/560	350
175/75R14C	99/98	T	-	618	177	5.0	775/750	475
185/75R16C	100/97	R	-	684	184	5.0	800/730	450
185R14C	102/100	R/P	-	652	189	5.5	850/800	450
195/70R15C	100/98/104/101	Q/R	-	655	201	6.0	800/750	450
195R14C	106/104	R/P	-	668	196	5.5	920/875	450
195R15C	106/104	R	-	693	196	5.5	920/875	450
205R14C	107/105	R	-	686	208	6.0	975/925	450
5.00R12LT	83/81	Q	-	568	143	3.50	487/462	450
6.50R15LT	106/101	L	-	730	185	5.5	950/825	550
6.50R16LT	107/102	M	-	750	185	5.5	975/850	450
7.00R16LT	115/110	L	-	775	200	5.5	1215/1060	670
165/70R13	79/83	T	XL	562	170	5.0	487	350
155R12LT	83/81	N	-	553	157	4.5	487/462	350
155R13LT	85/83	P/Q	-	578	157	4.5	487/462	350
165/70R13LT	88/86	P/R	-	562	170	5.0	560/530	375
165R13LT	89/88/94/93	P/R	-	594	165	4.5	580/560	350
175/75R14LT	99/98	T	-	?	?	5.0	775/750	475
185/75R16LT	100/97	R	-	684	184	5.0	800/730	450
185R14LT	102/100	R/P	-	652	189	5.5	850/800	450
195/70R15LT	100/98/104/101	Q/R	-	655	201	6.0	800/750	450

SUPERABRASION SERIES



G - 6 6 8



Comfort



Fuel-saving



Silence



Safety

Is specifically designed for Chinese roads.
In addition to ensuring excellent durability, the comfortability and reliable control performance of the vehicles and vehicles can be improved to the greatest extent.

Longer mileage, more wear – resistant.
The formula of tread rubber is optimized to improve wear life and ensure longer form distance.

Is safe and durable with high performance.
While improving the wear resistance, it meets the economic, safety and maneuverability requirements of compact cars.



G-668

Size	LI	SS	XL	Overall Diameter	Section Width	Standard Rim	Max. Load	Max. Pressure
				mm	mm		kg	kPa
165/70R13	79	T	–	562	170	5.0	437	300
175/70R14	84	H	–	602	177	5.0	500	300
185/60R14	82	H	–	578	189	5.5	475	300
185/60R15	84	H	–	603	189	5.5	500	300
185/65R15	88	H	–	621	189	5.5	560	300
195/55R16	87	V	–	620	201	6.0	545	300
195/60R14	86	H	–	590	201	6.0	530	300
195/60R15	88	H	–	615	201	6.0	560	300
195/60R16	89	H	–	640	201	6.0	580	300
195/65R15	91	V	–	635	201	6.0	615	300
205/55R16	91	H	–	632	214	6.5	615	300
205/65R15	94	H	–	647	209	6.0	670	300
175/70R14C	95/93	R	–	602	177	5.0	690/650	375
175/70R14LT	95/93	R	–	602	177	5.0	690/650	375
175R14C	99/97	R	–	636	177	5.0	775/730	450
175R14LT	99/97	R	–	636	177	5.0	775/730	450

AT-01

AT-01



Super grip performance on wet and dry ground, adapt to various road conditions.

Strong pattern block, overall enhance wear-resistant and stab-resistant.

Wide tread designed to increase the loading and griping capacity.

Zigzag in length and breadth deepen the grooves, enhance drain water and snow ability.

Size	LI	SS	XL	Overall Diameter	Section Width	Standard Rim	Max. Load	Max. Pressure
				mm	mm		kg	kPa
215/70R16	100	T	–	708	221	6.5	800	300
225/65R17	102	T	–	724	228	6.0	850	300
225/70R16	103	S	–	722	228	6.5	875	300
235/60R16	100	T	–	688	240	7.0	800	300
235/65R17	104	T	–	738	240	7.0	900	300
235/70R16	106	T	–	736	240	7.0	950	300
245/70R16	107	S	–	750	248	7.0	975	300
265/60R18	110	T	–	775	272	8.0	1060	300
LT215/75R15	100/97	S	–	703	216	6.0	800/730	350
LT235/75R15	104/101	S	–	733	235	6.0	900/825	350
LT245/75R16	120/116	Q	–	774	248	7.0	1400/1250	550
LT265/65R17	120/117	Q	–	776	272	8.0	1400/1285	550
LT265/70R16	110/107	Q	–	778	272	8.0	1060/975	350
LT275/65R17	121/118	Q	–	790	279	8.0	1450/1320	550

LIGHT-TRUCK TIRES
SUV TIRES



GT-02



GT-02



Wear



Fuel-saving



Handling



Safety

Super wear . resistant rubber tread designed , greatly enhanced the wear resistance of the tires.

Jagged central pattern design, greatly increase the tuning of the tire rigidity and durability performance.

Silicon-containing formula improves control and braking performance, reduces noise, reduces rolling resistance, reduces, heat generation and increases range.

Size	LI	SS	XL	Overall Diameter	Section Width	Standard Rim	Max. Load	Max. Pressure
				mm	mm		kg	kPa
31*10.50R15	109	S	–	775	268	8.5	1030	350
LT215/75R15	100/97	S	–	703	216	6.0	700/730	350
LT215/85R16	115/112	Q	–	772	216	6.0	1215/1120	550
LT225/75R15	102/99	S	–	719	223	6.0	850/775	350
LT225/75R16	115/112	Q	–	744	223	6.0	1215/1120	550
LT235/75R15	104/101	S	–	733	235	6.5	900/825	350
LT235/85R16	120/116	Q	–	806	235	6.5	1380/1260	550
LT245/70R17	119/116	Q	–	776	248	7.0	1360/1250	550
LT245/75R16	120/116	Q	–	774	248	7.0	1380/1260	550
LT245/75R17	121/118	Q	–	800	248	7.0	1450/1320	550
LT265/70R17	121/118	Q	–	804	272	8.0	1450/1320	550
LT265/75R16	123/120	Q	–	804	267	7.5	1550/1400	550
LT285/70R17	121/118	Q	–	932	292	8.5	1450/1320	550
LT285/75R16	126/123	Q	–	834	286	8.0	1700/1550	550
P215/70R16	99	T	–	708	221	6.5	775	300
P215/75R15	100	T	–	703	216	6.0	790	300
P225/70R16	101/103	T	–	722	228	6.5	825	300
P225/75R15	102	T	–	719	223	6.0	850	300
P225/75R16	104	T	–	744	223	6.0	900	300
P235/70R15	102	T	–	711	240	7.0	860	300
P235/70R16	107	T	XL	736	240	7.0	975	340
P235/75R15	108	T	XL	733	235	6.5	990	340
P235/75R15	109/108	T	XL	733	235	6.5	990	340
P245/70R16	111	T	XL	750	248	7.0	1090	340
P245/75R16	109	T	–	774	248	7.0	1030	300
P255/70R16	109	T	–	764	260	7.5	1030	300
P265/70R16	111	T	–	778	272	8.0	1090	300
P265/75R16	114	T	–	804	267	7.5	1180	300

OFF-ROAD SERIES

GS-03

GS - 03



Special wear resistant tread design , enhanced the wear resistance of tire.

Tight solid tire shoulder decorative pattern design, greatly enhanced the tuning precision of the tire.

Unique tread pattern groove design, ensuring the drainage performance and excellent grip of the tire.



Size	LI	SS	XL	Overall Diameter	Section Width	Standard Rim	Max. Load	Max. Pressure
				mm	mm		kg	kPa
P225/65R17	100/102	H	-	724	228	6.5	800	300
P235/65R17	103/104/108	H	XL	738	240	7.0	875	300
P245/65R17	105	H	-	750	248	7.0	925	300
P245/70R17	108	H	-	776	248	7.0	1000	300
P255/55R18	109	V	XL	737	265	8.0	1030	340
P265/65R17	110	H	-	776	272	8.0	1060	300
P265/70R17	113	H	-	804	272	8.0	1150	300
P265/70R18	114	H	-	819	272	8.0	1180	300
P275/55R20	117	H	XL	810	284	8.5	1285	340
P275/60R20	114	H	-	838	279	8.0	1180	300
P275/65R18	114	H	-	815	279	8.0	1180	300
P285/65R17	115	H	-	802	292	8.5	1215	300

OFF-ROAD SERIES



GF-50



Braking



Silence



Handling



Safety

Excellence performance on any roads.

Optimized pattern design, suitable for high- performance SUV, excellently durable and quiet on any road.

Silicon-containing formula improves control and braking performance, reduces noise, reduces rolling resistance, reduces heat generation and increases range.



GF-50

Size	LI	SS	XL	Overall Diameter	Section Width	Standard Rim	Max. Load	Max. Pressure
				mm	mm		kg	kPa
LT215/75T15	100/97	Q	-	703	216	6.0	800/730	350
LT225/75R15	102/99	S	-	719	223	6.0	850/775	350
LT235/70R16	104/101	Q	-	736	240	7.0	900/825	350
LT235/75R15	104/101	Q	-	733	235	6.5	900/825	350
LT235/85R16	120/116	Q	-	806	235	6.5	1380/1260	550
LT245/75R16	120/116	Q	-	774	248	7.0	1400/1250	550
LT265/65R17	120/117	Q	-	776	272	8.0	1400/1285	550
LT265/70R16	110/107	Q	-	778	272	8.0	1060/975	350

SPECIAL FOR TOP CLASS OFF-ROAD
TEAM AND REFIT VEHICLE



GM-02



Wear



Safety



Handling



Fuel-saving

Huge pattern block and pattern groove optimization combination design, provide excellent non-paved road driving force, grip and anti-skid performance.

Double-ply reinforced belts and special specification three-ply reinforced tire body design, which greatly increases the overall strength of tires to meet the requirements of the worst road conditions.

Specific protection dam design of tire shoulder pattern and reinforcement design of rough mineral tire to improve the impact resistance of shoulder, thus greatly improving the durability.

Single twined hexagonal tyre design greatly improves the durability of the tyre rim.



GM-02

Size	LI	SS	XL	Overall Diameter	Section Width	Standard Rim	Max. Load	Max. Pressure
				mm	mm		kg	kPa
33*12.50R15LT	108	Q	-	826	318	10	1000	250
33*12.50R17LT	114	Q	-	826	318	10	1180	350
33*12.50R18LT	118	Q	-	826	318	10	1320	450
33*12.50R20LT	114	Q	-	826	318	10	1180	450
35*12.50R17LT	121	Q	-	877	318	10	1450	450
35*12.50R17LT	121	Q	-	877	318	10	1450	450
35*12.50R18LT	123	Q	-	877	318	10	1550	450
35*12.50R18LT	123	Q	-	877	318	10	1550	450
35*12.50R20LT	121	Q	-	877	318	10	1450	450
35*12.50R20LT	121	Q	-	877	318	10	1450	450
LT235/85R16	120/116	Q	-	806	235	6.5	1400/1250	550
LT265/70R17	121/118	Q	-	778	272	8.0	1450/1320	550
LT265/70R17	121/118	Q	-	778	272	8.0	1450/1320	550
LT265/75R16	123/120	Q	-	804	267	7.5	1550/1400	550
LT275/65R18	123/120	Q	-	815	279	8.0	1550/1400	550
LT275/65R18	123/120	Q	-	815	279	8.0	1550/1400	550
LT285/70R17	121/118	Q	-	832	292	8.5	1450/1320	550
LT285/70R17	121/118	Q	-	832	292	8.5	1450/1320	550
LT285/75R16	126/123	Q	-	834	286	8.0	1700/1550	550



W705



W 7 0 5



Winter



Drainage



Braking



Handling

Under precision calculation, W705 pattern ensures good maneuverability and low noise.

Use of special rubber formula improves the wet grip and skid resistance.

Unique pattern design avoids irregular tread wear of road.

Silicon-containing formula improves control and braking performance, reduces noise, reduces rolling resistance, reduces heat generation and increases range.

Size	LI	SS	XL
155/65R13	79	Q	-
165/70R13	79	T	-
175/65R14	82	T	-
175/70R13	82	T	-
175/70R14	84	T	-
185/60R14	82	T	-
185/60R15	84	T	-
185/65R14	86	T	-
185/65R15	88	T	-
185/70R14	88	T	-
195/50R15	82	T	-
195/55R15	85	T	-
195/60R15	88	T	-
195/60R16	89	T	-
195/65R15	91	T	-
205/55R16	91	T	-
205/60R16	92	T	-
205/65R15	94	T	-
205/70R15	96	Q	-
215/45ZR17	91	T	-
215/55R17	94	T	-
215/60R16	95	T	-
215/60R17	96	T	-
215/65R16	98	T	-
215/70R16	100	T	-
225/45R17	91	H	-
225/50R17	98	S	XL
225/55R16	95	T	-

Size	LI	SS	XL
225/55R17	97	S	-
225/60R17	99	T	-
225/65R17	102	S	-
225/70R16	103	T	-
235/55R17	103	T	XL
235/60R18	103	S	-
235/65R17	108	T	XL
235/70R16	106	T	-
245/45R18	100	S	XL
265/65R17	112	S	-
285/65R17	116	S	-
165R13C	94/93	Q	-
175R13C	97/95	Q	-
185/75R16C	100/97	Q	-
185R14C	102/100	Q	-
185R15C	103/102	R	-
195/70 R15C	99/96	Q	-
195R14C	106/104	Q	-
195R15C	106/104	Q	-
215/70R15C	109/107	Q	-
225/75R16C	115/112	Q	-
LT215/75R15	100/97	Q	-
LT235/75R15	104/101	Q	-
165R13LT	94/93	Q	-
185/75R16LT	100/97	Q	-
185R14LT	102/100	Q	-
185R15LT	103/102	R	-
215/70R15LT	109/107	Q	-
225/75R16LT	115/112	Q	-



W 7 6 6



Winter



Drainage



Braking



Handling

The large block pattern designs improve tire handling performance.

The crossed trench design provide stable gripping in the snow road.

Dense 3D pattern design for excellent gripping and control performance against snow.

The multi-pitch pattern block designs by computer simulation analysis of reasonable arrangement, effective reduce the tire noise.



W766

Size	LI	SS	XL	Overall Diameter	Section Width	Standard Rim	Max. Load	Max. Pressure
				mm	mm		kg	kPa
195/55R16	91	T	XL	620	201	6.0	615	340
215/50R17	95	T	XL	648	226	7.0	690	340
215/55R16	97	T	XL	642	226	7.0	730	340
215/55R18	99	H	-	693	226	7.0	690	300
225/40R18	92	T	XL	637	230	8.0	630	340
225/45R18	95	T	XL	659	225	7.5	690	340
225/50R18	99	T	XL	683	233	7.0	775	340
225/55R19	99	T	-	731	233	7.0	775	300
225/60R18	104	T	XL	727	228	6.5	900	340
235/45R17	97	T	XL	644	236	8.0	730	340
235/50R18	101	T	XL	693	245	7.5	825	340
235/50R19	103	T	XL	719	245	7.5	875	340
235/55R18	104	H	XL	715	245	7.5	900	340
235/55R19	105	H	XL	741	245	7.5	925	340
245/50R20	102	T	-	754	253	7.5	850	300
245/55R19	103	H	-	753	253	7.5	875	300
245/60R18	105	T	-	751	248	7.0	925	300
245/70R16	111	T	XL	750	248	7.0	1090	340
255/45R19	104	H	XL	713	255	8.5	900	340
255/50R19	107	T	XL	739	365	8.0	975	340
255/55R18	109	T	XL	737	265	8.0	1030	340
255/55R19	111	H	XL	763	265	8.0	1090	340
265/60R18	114	H	-	775	272	8.0	1180	340
265/70R16	112	H	-	778	272	8.0	1120	300
275/45R20	110	T	XL	756	273	9.0	1060	340
275/55R20	117	T	XL	810	284	8.5	1285	340
275/65R18	116	T	-	815	279	8.0	1250	300
285/50R20	116	T	XL	794	297	9.0	1250	340
285/60R18	120	T	XL	799	292	8.5	1400	340



W 6 9 6



Comfort



Fuel-saving



Drainage



Handling

Unique design for higher load handling, The reasonable tooth – shaped rim design makes the performance of the tire better under high load.

Rigid pattern distribution for long life, Designed with a central pattern, a solid tire body ensures traction and durability.

Excellent snow brake, safe and reliable, Three wide pattern grooves are designed to provide better drainage and ensure optimal snow braking performance.



W 6 9 6

Size	LI	SS	XL	Overall Diameter	Section Width	Standard Rim	Max. Load	Max. Pressure
				mm	mm		kg	kPa
6.50R16LT	107/102	R	–	755	182	4.5	975/850	550
7.00R16LT	115/110	N	–	778	603	5.5	1215/1060	670

HIGH PERFORMANCE TIRES

BRAVES AU518



Better driving and handing performance.

The pattern is specially designed for improving the performance of driving, controlling and dry wetland.

Silicon-containing formula improves control and braking performance, reduces noise, reduces rolling resistance, reduces heat generation and increases range.



BRAVES AU518

Size	LI	SS	XL
205/55R16	91	V	-
225/45ZR18	95	W	XL
235/45ZR18	98	W	XL
245/45ZR18	100	W	XL
255/45ZR18	103	W	XL
235/50ZR18	101	W	XL
245/50ZR18	104	W	XL
215/55ZR18	99	W	XL
225/55ZR18	102	W	XL
235/55ZR18	104	W	XL
255/40ZR19	100	W	XL
275/40ZR19	105	W	XL
245/45ZR19	102	W	XL
255/45ZR19	104	W	XL
235/50ZR19	103	W	XL
255/50ZR19	107	W	XL

Size	LI	SS	XL
235/55ZR19	105	W	XL
245/55ZR19	103	W	-
275/55ZR19	111	W	-
295/35ZR20	105	W	XL
265/40ZR20	104	W	XL
245/45ZR20	103	W	XL
255/45ZR20	105	W	XL
275/45ZR20	110	W	XL
245/50ZR20	102	W	-
255/50ZR20	109	W	XL
275/50ZR20	113	W	XL
285/50ZR20	116	W	XL
255/55ZR20	110	W	XL
275/45ZR21	110	W	XL
275/40ZR22	107	W	XL



LX - 50



Wear



Fuel-saving



Handling



Safety

Super wear . resistant rubber tread designed , greatly enhanced the wear resistance of the tires.

Jagged central pattern design, greatly increase the tuning of the tire rigidity and durability performance.

Silicon-containing formula improves control and braking performance, reduces noise, reduces rolling resistance, reduces , heat generation and increases range.



LX-50

Size	LI	SS	XL	Overall Diameter	Section Width	Standard Rim	Max. Load	Max. Pressure
				mm	mm		kg	kPa
225/70R15C	112/110	R	-	697	228	6.5	1120/1060	450
215/75R14C	112/110	R	-	678	216	6.0	1120/1060	475